Gabinete para Servidores 42U (600mm Ancho X 1000mm Profundidad)



| Rating: Not Rated Yet Price: |
|-------------------------------|
| Variant price modifier: |
| Base price with tax: |
| Price with discount: |
| Salesprice with discount: |
| Sales price: |
| Sales price without tax: |
| Discount: |
| Tax amount: |
| |

Ask a question about this product

Manufacturer: Techmaster

Description

Features:

- Reliable structure. static loading capacity: 500KG(Optional castors and plinth)
- Adjustable feet and heavy duty castors are avilable simultaneously, moving conveniently and fixing reliably.
- Baying together easily, quickly, efficiently and firmly.

High density vented arc front and rear doors (patent), excellent and elegant exterior design;

comprehensive consideration of balances of ventilation, exterior door hinge with 180 degrees, the

door can be opened to 180 degrees though connected, easily assembled and operated.

Optional cable entry on top cover and bottom panel. Front, rear doors and side panels can be

removed facility, the bottom has the function of ventilation and rat-proof.

Varies of optional accessories, reliable quality.

Optional opening hole and varies of specification upon customers' special requirements.

4 heights - 27U, 32U, 37U, 42U

Flexible packing methods allows for convenient stocking and end user delivery.

Multiple sizes available.

Customization requests welcome

Standard and Material:

Comply with ANSI/EIA,RS-310-D;IEC297-2;DIN41491:PART1;
DIN41494:PART7;GB/T3047.2-92 standard and ETSI standard.
Surface Finish: Degreasing, pickling, phosphoric, power coating.
Material: SPCC cold rolled steel or EG steel.
Thickness: Mounting profile 2.0mm,others:1.2-1.5mm
Color: RAL9005(black) ;RAL7044(grey)